The management and control system for the modern pig - and poultry production




drawings in this brochure

GB

OptiLink

OptiLink - the management and control system for permanent data acquisition, real-time control and monitoring of pig- and poultry houses, from virtually any location in the world.

OptiLink is the name of OPTICON's innovative management and control system for modern pig and poultry production. Its software is based on modern communication technology. All farms, even if they are located at different places, can be controlled and monitored from a single central PC. Additional features include the ability to graphically visualize all houserelated measuring and production data in real time.





Use of modern network technologies....

The basic unit ACT-20 is the intelligent interface between your individual controls like climate, automatic bird weighing and the feed computer in each individual house.

In every individual controller, you need a small additional interface board.



Data processing and graphical visualization of the entire house and production data.


What happens if you don't realize what's happening? OptiLink collects a great variety of data, which can easily and quickly be processed by your office PC. Feed consumption, feed/ water ratio, feed conversion, mortality, uniformity, hours of heating and of course your complete climate control are made visible to you in tables and charts. All gathered data can be illustrated as curves and can be combined freely by just one mouse click.

Your own farm-specific data processing, no problem thanks to OptiLink

Thanks to its flexibility, OptiLink enables you to import data into any MS-Office application, such as Excel, Word or Power Point.

OptiLink offers you the following excellent features and benefits:

- use of a report printer;
- use of a data transmission modem;
- alarm messages via SMS or e-mail (future option);
- remote control and maintenance via telephone;
- use of Radio Modems;
- use of GSM Modems;
- various interfaces for external, own data processing.



Make your own information screen

When you prefer all the most important real time data to be displayed on one single screen or printed at preset intervals, Optilink has the answer. Just drag and drop the relevant data into the special screen and OptiLink makes this to work.

and the same local and an end of the same state of the same stat	.xx - PAGE: 01 - GENERAL SETTINGS				- 01
🕈 📮 📑 🖏 🔺 🔺 🛛 Beload	1 2 C 2 2 3 3 3 3 3 3 2 C				
OLO - ACT 30 TERMINAL - 02-4 OL - OSCHAL SETTINGS OL - INSTALLERS SETTINGS OL - NOC10 CONTROLLER	Base		Value		
	COL time			Ids. un	
	02 date			dd_ma	
	03 year		2003		
	D4 display		2	marinen	
	- A set of the set of				
	Of mode time-out alarm		2	on reset	
	06 mode ACT-20 alarm		.0	24342	
	07 type of ACT-20 alara		a	no alara	
	no cibe of wor-to stars				
DEP: 80.00 - MCC 10 CONTROLLER					00
🕞 🗗 🖡 🔹 🖪 Belowd					
Billion NCC-10 CONTROLLER	PAGE 10 - FAN CONTROL A1	Value	Test		[0]
Billion B	PAGE 10 FAN CONTROL A1	σ	Test		
B [•] B• B• B• Belowd Belowd Boo-MCC-10 CONTROLLER B 02-COMMON SETTINGS MCC-10 D 3-SETTINGS/MCASUREMENTS	PAGE 10 - FAN CONTROL A1 Tr Cr Cr D A 7 C 7 C Name 01 Home 02 Hannal setting	o sa	Teat.		
B B B B B B B B B B B B B C COMMON SETTINGS MC-10 C C S TIMSS-MEASUREMENTS D C M-NNMAX: REGISTRATIONS	PAGE 10 FAN CONTROL A1	σ	Test		
B [•] B• B• B• Belowd Belowd Boo-MCC-10 CONTROLLER B 02-COMMON SETTINGS MCC-10 D 3-SETTINGS/MCASUREMENTS	PAGE 10 FAN CONTROL A1 Tr Ch Ch A CONTROL A1 Tr Ch Ch A CONTROL A1 DE Hods control 02 Haunal cetting 03 Owbpide temperature	0 02 02 8,86	Test off %		
BORNACTIO CONTROLLER OR-COMMON SETTINGS MCC-10 OR-SETTINGS MCC-10 OR-SETTINGS MCC-10 OR-NIN-MAX REGISTRATIONS OR-NIN-MAX REGISTRATION	PAGE 10 - FAN CONTROL A1 T C A C 7 C 7 Di Hanal setting 03 Oxbaide temperature 05 Setpoint room temperature	0 50 38,8 0,4	Teat. off * *c		60
10 - MCC10 CONTROLLER 10 - COMMON SETTINGS MCC10 10 - SETTINGS MCC100 10 - SETTINGS MCC100 10 - NONMOX REGISTRATIONS 10 - NONMOX REGISTRATIONS 10 - NONMOX REGISTRATIONS 10 - FAN CONTROL 10 - FAN CONTROL 10 - FAN CONTROL	PAGE: 10 - FAN CONTROL A1 Tr C A A CONTROL A1 Tr C A A C A C A C A Base 01 Hods control 03 Owinide temperature 04 Setpoint room temperature 04 Setpoint room temperature	0 50 38,8 0,4 0,0	Teat		(10)
BOO-NCC10 CONTROLLER BOO-NCC10 CONTROLLER BO-NCC10 CONTROLLER CONNON SETTINGS MCC10 CO-NGST VARIATION OO-NGST VARIATION OON TOOL OO	PAGE 10 - FAN CONTROL A1 T Q D A 7 C 7 United Control Vanas 01 Blobs control 02 Hanual cetting 03 Oxiside temperature 04 Setpoint room temperature 04 Highy variationest temperature 04 Highy variationest temperature	0 50 58,8 0,4 0,0 0,9	Test oct %c *c *c *c		
2000-MCC-10 CONTROLLER 20.00-MCC-10 CONTROLLER 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 00-SETTINGS-MCC-100 10-SETTINGS-MCC-100 10-SETTINGS-MCC-100 11-SETINGS-MCC-100 11-SETINGS-MCC-100 11-SETINGS-MCC-100	PAGE 10 - FAN CONTROL A1 T 2 A 7 3 7 Name OS Hounds setting OS Hounds setting OS Setpoint room temperature OS Setpoint room temperature OS Higher variationrel.temi OF Har.temp.variationrel.temi OS Calc.temp.variationrel.temi	0 50 38,8 0,4 0,0 0,9 0,0	Tean off to to to to to to		
BOD-MCC10 DON'HOLLER BOD-MCC10 DON'HOLLER BOD-MCC10 DON'HOLLER DO-MCM-SETTINGS MC-100 TO-SETTINGS-MCS100 DO-NGM-TVARIATION DO-NGM-TVARIATION DO-NGM-TVARIATION DO-NGM-TVARIATION DO-NGM-TVARIATION DO-NGM-CONTROL TO-FAN CONTROL TO-FAN CONTROL A2 DI 13-FAN CONTROL A3 DI 13-FAN CONTROL A4	PAGE 10 - FAN CONTROL A1 T C A D A 7 C 7 C Name 0. Hannal setting 0. Orbride temperature 0. Steppint roce temperature 0. Steppint roce temperature 0. Steppint roce temperature 0. Steppint roce temperature 0. Steppint to constitute	0 50 30,0 0,4 0,0 0,3 0,0	Team off %c %c %c %c %c		
BLOO-MCC-10 CONTROLLER BLOO-MCC-10 CONTROLLER D. CO-CUMMON SETTINGS MCC-100 CO-SETTINGS MCC-100 CO-MICHINGS MCC-100 CO-MICHINGS MCC-100 CO-MICHINGS MCC-100 CO-MICHINGS MCC-100 CO-MICHINGS MCC-100 CO-MICHINGS MCC-100 TO-FAN CONTROL A1 TI-FAN CONTROL A3 TI-FAN CONTROL A3 TI-FAN CONTROL A4 TI-FAN CONTROL A5	PAGE 10 - FAN CONTROL A1 T C A C C C C C C C C C C C C C C C C C	0 50 38,8 0,4 0,0 0,5 0,0 0,0 0,0	Tean off to to to to to to		
to - SET THISS MEASUREMENTS to - RET THISS MEASUREMENTS to - REFT VARIATION to - REFT	PAGE 10 - FAN CONTROL A1 T C A D A 7 C 7 C Name 0. Hannal setting 0. Orbride temperature 0. Steppint roce temperature 0. Steppint roce temperature 0. Steppint roce temperature 0. Steppint roce temperature 0. Steppint to constitute	0 50 30,0 0,4 0,0 0,3 0,0	Teat		

All advantages at a glance

- Monitoring and control of the houses in real time whenever the farm manager changes the computer settings, the changes take effect immediately in the house;
- Central data storage and processing per animal comparison with reference data stored in the system;
- Integrated report system by e-mail;
- Alarm system via e-mail and SMS respectively (future option);
- Permanent visualization of house data on your PC;
- Easy choice of different languages;
- High degree of flexibility.



ruby360.ca



40 Woodstock St. N., Tavistock, ON N0B 2R0

sales@ruby360.ca